

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** Covering lacquer red

Abdecklack rot

· **Article number:**

86900134

86943000 = 100g

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Not approved for private consumers.

· **Application of the substance / the mixture** Masking material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Heimerle + Meule GmbH  
Dennigstrasse 16  
D-75179 Pforzheim

Telefon +49 (0) 7231 940-0  
Telefax +49 (0) 7231 940-2199  
www.heimerle-meule.com

· **Further information obtainable from:**

Abteilung BASU - Bau/Arbeitssicherheit/Umwelt  
Department BASU - Construction / Occupational Safety / Environment  
sds@heimerle-meule.com

IATA - 24h Emergency Contact - IATA - 24h Emergency Contact -  
(Dangerous goods emergency number)  
+49 172 739 6970

· **1.4 Emergency telephone number:**

DEUTSCHLAND - GERMANY:

Vergiftungs-Informationen-Zentrale Freiburg, ++49 761 19240 (24 h)  
(Poisoning Information Center)

GREAT BRITAIN:

National Poisons Information Service +44 121 507 4123

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111 - In Scotland: NHS 24 - dial 111

ITALY:

Istituto Superiore di Sanità +3906499906140

KROATIA - REPUBLIKA HRVATSKA:

(+385) 01 2348 342

ESTLAND - ESTONIA:

Tervisemeti Mürgistusteabekeskuse 16662, (+342) 7914 794

LETTLAND - LATVIA:

Latvijas Vides, ģeoloģijas un meteoroloģijas centrs (+371) 670 32600

LITAUEN - LIETUVOS RESPUBLIKA:

Apsinuodijimų informacijos biuras +370 (85) 2362052

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 1)

## SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS05



GHS07



GHS08

- Signal word *Danger*
- Hazard-determining components of labelling:  
butanol  
n-butyl acetate  
ethylbenzene
- Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 2)

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Labelling of packages where the contents do not exceed 125 ml**

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

butanol

n-butyl acetate

ethylbenzene

· **Hazard statements**

H318 Causes serious eye damage.

· **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components / Information on ingredients:**

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000	n-butyl acetate; Butyl acetate; 1-Acetoxybutane; Acetic acid, butyl ester; Butyl ethanoate; TBAC ----- ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	25-<50%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000	xylene (mix); xylene, mixture of isomers; xylene, mixed isomers, pure; xylene ----- ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	12.5-<20%

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 3)

CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 RTECS: NP 9625000	butanol; 2-methylpropan-1-ol; butyl alcohol (except tert-butyl alcohol); iso-butanol; Isobutyl alcohol; 1-Propanol, 2-methyl-; Isopropyl carbinol ----- ☠ Flam. Liq. 3, H226 ☞ Eye Dam. 1, H318 ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	12-<12.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 RTECS: DA 0700000	ethylbenzene ----- ☠ Flam. Liq. 2, H225 ☞ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ----- ☠ Flam. Liq. 3, H226	3-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · **General information:**

Immediately remove any clothing soiled by the product.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

Involve doctor immediately after an accident or unwell

##### · **After inhalation:**

Seek medical treatment in case of complaints.

Take affected persons into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

##### · **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

##### · **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

##### · **After swallowing:**

Drink plenty of water and provide fresh air. Call for a doctor immediately.

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

#### · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

##### · **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

##### · **For safety reasons unsuitable extinguishing agents:** Water with full jet

#### · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

#### · 5.3 Advice for firefighters

##### · **Protective equipment:** Mount respiratory protective device.

GB

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 4)

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Only handle and refill product in closed systems.

· **6.2 Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

the usual precautionary measures are to be adhered to when handling chemicals.

Prevent formation of aerosols.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Do not dry clean dust covered objects and floors. Wash thoroughly with plenty of water.

· **Information about fire - and explosion protection:**

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings .

Observe official regulations on storing packagings .

Prevent any seepage into the ground.

-

· **Information about storage in one common storage facility:**

Store away from flammable substances.

Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store under lock and key and out of the reach of children.

· **Storage class: 3**

· **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 5)

## · 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:****CAS: 123-86-4 n-butyl acetate**

WEL (Great Britain)	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
IOELV (European Union)	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
AGW (Germany)	Long-term value: 300 mg/m <sup>3</sup> , 62 ppm 2(I);AGS, Y

**CAS: 1330-20-7 xylene (mix)**

WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
IOELV (European Union)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
AGW (Germany)	Long-term value: 440 mg/m <sup>3</sup> , 100 ppm 2(II);DFG, EU, H

**CAS: 78-83-1 butanol**

WEL (Great Britain)	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm Long-term value: 154 mg/m <sup>3</sup> , 50 ppm
AGW (Germany)	Long-term value: 310 mg/m <sup>3</sup> , 100 ppm 1(I);DFG, Y

**CAS: 100-41-4 ethylbenzene**

WEL (Great Britain)	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
IOELV (European Union)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin
AGW (Germany)	Long-term value: 88 mg/m <sup>3</sup> , 20 ppm 2(II);DFG, H, Y, EU

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

WEL (Great Britain)	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
IOELV (European Union)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin
AGW (Germany)	Long-term value: 270 mg/m <sup>3</sup> , 50 ppm 1(I);DFG, EU, Y

· **Regulatory information**

WEL (Great Britain): EH40/2020  
IOELV (European Union): (EU) 2019/1831  
AGW (Germany): TRGS 900

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 6)

<b>· Ingredients with biological limit values:</b>	
<b>CAS: 1330-20-7 xylene (mix)</b>	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
BGW (Germany)	1.5 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Xylol
	2000 mg/L Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Methylhippur-(Tolur-)Säure (alle Isomere)
<b>CAS: 100-41-4 ethylbenzene</b>	
BGW (Germany)	250 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Mandelsäure plus Phenoxyglyxylsäure

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

According to EC Directive 89/686/EEC

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device when high concentrations are present.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Beware: Filter masks provide protection for a short period of time only. They should only be used in exceptional cases, that is if a small amount of the substance has spilled out or in order to fight spillages and fire.

according EN 14387

according to EN 143

· **Recommended filter device for short term use:** Combination filter A-P1

· **Protection of hands:**

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.



Protective gloves

according to EN 374

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 7)

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

Sensibilisation by the components in the glove materials is possible.

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Prior to working with gloves the rubbing in with tanniferous skin-protecting agents for the avoidance of skin softening due to perspiration is recommended.

· **Material of gloves**

PVC or PE gloves

Recommended thickness of the material:  $\geq 0.4$  mm

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 120 - 240 minutes (Permeation according to EN 16523-1:2015: Level 4).

Value for the permeation: Level  $\leq 3$

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 3).

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong material gloves

· **Eye protection:**



Tightly sealed goggles

according to EN 166

· **Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: Red

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 107°C (224.6°F)

· **Flash point:** 23 - 60°C (73.4 - 140°F)

· **Flammability (solid, gas):** Not applicable.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 8)

· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	1.7 Vol %
· <b>Vapour pressure at 20°C (68°F):</b>	6.9 hPa (5.2 mm Hg)
· <b>Density at 20°C (68°F):</b>	0.97 g/cm <sup>3</sup> (8.09 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20°C (68°F):</b>	80 s (ISO 6 mm)
· <b>Solvent separation test:</b>	< 3 %
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	~68 %
<b>Solids content:</b>	32 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Nitrogen oxides  
Carbon monoxide and carbon dioxide

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**ATE (Acute Toxicity Estimates)**

Dermal	LD50	10,000–16,000 mg/kg (rbt)
--------	------	---------------------------

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 9)

Inhalative	LC50/4 h	110–220 mg/l
<b>CAS: 123-86-4 n-butyl acetate</b>		
Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)
<b>CAS: 1330-20-7 xylene (mix)</b>		
Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	6,350 mg/l (rat)
<b>CAS: 78-83-1 butanol</b>		
Oral	LD50	2,460 mg/kg (rat)
Dermal	LD50	4,200 mg/kg (rbt)
<b>CAS: 100-41-4 ethylbenzene</b>		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)
Inhalative	LC50/4 h	11 mg/l (ATE)
<b>CAS: 108-65-6 2-methoxy-1-methylethyl acetate</b>		
Oral	LD50	8,500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020


**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 10)

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

- **Waste disposal key:**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

- **European waste catalogue**

There are no uniform EC regulations for the disposal of chemicals or residues. Chemical residues generally count as special waste. The disposal of the latter is regulated in the EC member countries through corresponding laws and regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose of special waste

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- **Uncleaned packaging:**

- **Recommendation:**

Disposal must be made according to official regulations.

Packaging which is uncleaned or soiled with product remains is to be treated like the product itself

Packaging free of product remains is to be supplied refuse for recycling. Only if no adequate collecting system is available, they may be disposed of through the domestic rubbish

### SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1263

- **14.2 UN proper shipping name**

- **ADR**

UN1263 PAINT

- **IMDG, IATA**

PAINT

(Contd. on page 12)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 11)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids.  
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

· **Hazard identification number (Kemler code):** Warning: Flammable liquids.  
30  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml  
· **Transport category** 3  
· **Tunnel restriction code** D/E  
· **Remarks:** 2.2.3.1.5.1: < 450l kein Gefahrgut / no dangerous goods

· **IMDG**

· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **IATA**

· **Remarks:** 24h emergency contact -  
(Dangerous goods emergency number)  
  
+49 172 739 6970

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

COUNCIL DIRECTIVE 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work (fourteenth individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC)

(Contd. on page 13)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 12)

*DIRECTIVE 2012/18/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC*

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **GADSL - Global Automotive Declarable Substance List**

CAS: 9004-70-0	nitrocellulose solutions, with not more than 12.6% nitrogen, by dry mass, and not more than 55% nitrocellulose	D(FI)
CAS: 100-41-4	ethylbenzene	D(FI)

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	97.5

· **Waterhazard class:** .

· **Other regulations, limitations and prohibitive regulations -**

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Reasons for revise**

*If necessary, this safety data sheet can revised according to legal guidelines.*

*Our current version for your reference is available on our website  
[www.heimerle-meule.com](http://www.heimerle-meule.com)*

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.*
- H226 Flammable liquid and vapour.*
- H304 May be fatal if swallowed and enters airways.*
- H312 Harmful in contact with skin.*
- H315 Causes skin irritation.*
- H318 Causes serious eye damage.*
- H332 Harmful if inhaled.*
- H335 May cause respiratory irritation.*
- H336 May cause drowsiness or dizziness.*
- H373 May cause damage to organs through prolonged or repeated exposure.*

· **Department issuing SDS:**

*Abteilung BASU - Bau/Arbeitssicherheit/Umwelt*

(Contd. on page 14)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date: 30.10.2020

Version number 12

Revision: \_\_\_\_\_ 30.10.2020

**Trade name: Covering lacquer red**  
**Abdecklack rot**

(Contd. of page 13)

Department BASU - Construction / Occupational Safety / Environment

sds@heimerle-meule.com

**Contact:**

Herr Thomas Knuth

Knuth@heimerle-meule.com

sds@heimerle-meule.com

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

AwSV: Ordinance on facilities for handling water-polluting substances (German regulation).

TRGS: Technical rules for hazardous substances (German regulation)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

\* **Data compared to the previous version altered.**